

# FK 67 PVA GREEN

## Film Forming Release Agent

### Description

The **FK 67 PVA GREEN** is an external release agent, silicon free, to apply on models or moulds of all kinds (plaster, wood, resin, metal, mastic). It creates a sealed film isolating the mould. It allows the release of the polyester, epoxy, and vinylester resins

### Advantages

The external release agent **FK 67 PVA GREEN** is a liquid release agent which evaporates at room temperature and then form a film which sticks to the mould all the way to the release.

The **FK 67 PVA GREEN** is a high concentrated polyvinyl alcohol, tinted for a better visual control. It can be diluted with water or alcohol if you want a fast dry

The external release agent **FK 67 PVA GREEN** is silicon and wax free, allowing varnishing or gluing on released moulds.

Apply for each mould

Clean the mould or released part with water or compressed air

### Application

1. Clean the mould with the cleaner CIREX Si 19 or an efficient degreaser
2. Apply with a spray gun or a brush 3 crossed coats
3. Leave the film to dry for 2 hours minimum at 20°C (depending on support)

### Special precaution

Use in a well ventilated area

Wear gloves and mask with cartridges if applying with spray gun.

### Packaging

1 Liter	19 Liters
---------	-----------

**LEGAL NOTES:** SICOMIN reserves the right to change the properties of its products. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data and tolerance may vary due to circumstances beyond our control. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

**MENTIONS LÉGALES :** SICOMIN se réserve le droit de modifier les propriétés du produit. Toutes les caractéristiques spécifiées dans cette Fiche technique sont basées sur des tests de laboratoire. Les mesures et leurs tolérances effectives peuvent varier pour différentes raisons. SICOMIN se réserve le droit Aucune garantie de quelque nature que ce soit, sauf que les matériaux fournis sont de qualité standard. Tous les risques et responsabilités découlant de la manutention, le stockage et l'utilisation des produits, ainsi que le respect des restrictions légales applicables, incombe à l'utilisateur.