

# INFULIGNE Slow Black

## General Characteristics

The Infuligne Slow Black is a flat geometry resin channel to avoid marking vacuum infusion parts and limit exothermies.

The Infuligne Black consists of a three-dimensional polyester filament core, wrapped in a non-woven polyester sheath.

Easy to cut to the desired size and flexible, it allows a very fast installation of resin diffuser channels

## Features

Resin speed : slow

- ⇒ Width 5 and 10cm
- ⇒ Temperature 80°C
- ⇒ Thickness 4mm
- ⇒ Color : grey/black
- ⇒ Compatible with epoxy, polyester and vinylester resins

## Packaging

Infuligne Black is available in 100lm rolls

## Tips and tricks

**Infuligne Slow Black** can be overlapped. To maximize resin flow, cut away the protective sleeve at the overlap.

Binding is possible with Sealtex S2, sticky tape, hot melt glue or plastic staples



**LEGAL NOTES:** SICOMIN reserves the right to change the properties of its products. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data and tolerance may vary due to circumstances beyond our control. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

**MENTIONS LÉGALES :** SICOMIN se réserve le droit de modifier les propriétés du produit. Toutes les caractéristiques spécifiées dans cette Fiche technique sont basées sur des tests de laboratoire. Les mesures et leurs tolérances effectives peuvent varier pour différentes raisons. SICOMIN ne donne aucune garantie de quelque nature que ce soit si ce n'est que les matériaux fournis sont de qualité standard. Tous les risques et responsabilités découlant de la manutention, le stockage et l'utilisation des produits, ainsi que le respect des restrictions légales applicables, incombe à l'utilisateur.