



# FOAMING SYSTEMS



©CAYOTRIMAGE

It's all in the Chemistry

[www.sicommin.com](http://www.sicommin.com)



## FOAMING SYSTEMS

Sicomini's 2 part epoxy foams offer uniform density closed cell cores from 170-600 kg/m<sup>3</sup> with different hardeners providing a range of curing times and expansion rates. CFC free and highly adaptable, Sicomin foaming systems produce versatile cores and excellent laminate skin bonding.

## TOP PRODUCTS

### PB 170, 250, 400 & 600 / DM OX

Foaming systems for closed cell epoxy foams from 170 to 600 kg/m<sup>3</sup>

Densities obtained are approximately 170, 250, 400 and 600 kg/m<sup>3</sup> respectively (open mould expansion at 23C)

Standard foam colour is white but can be coloured with epoxy compatible pigments

The mixed components react in 2 stages; gentle expansion followed by slow hardening of the foam

Adheres to a wide range of materials

Can be poured onto and co-cured with prepregs or other epoxy laminates

CFC free and highly water resistant



### PB 270 i, PB 370 i & PB 570 i

Self-extinguishing 2 component epoxy foaming system

Densities obtained are approximately 270, 370 and 570 kg/m<sup>3</sup> respectively (open mould expansion at 23C)

Standard foam colour is white but can be coloured with epoxy compatible pigments

The mixed components react in 2 stages; gentle expansion followed by slow hardening of the foam

Adheres to a wide range of materials

Can be poured onto and co-cured with prepregs or other epoxy laminates

CFC free and highly water resistant

Complies with industry FST classifications: Aerospace FAR 25-853 and Rail EN45-545



## Features and Benefits

- Largest range of multiple density foaming systems
- For strong, high quality and versatile cores
- Superior bonding of laminate skins (epoxy, polyester, vinylester)
- Low pressure, controlled expansion
- Closed cell with no shrinkage after hardening or water uptake
- Adaptable to multiple production requirements and environments
- Fire retardant and fast curing versions available
- Machine dispensable options available for large series production runs

Sicomini  
31 avenue de la Lardière  
13220 Châteauneuf les Martigues  
France  
T: +33 (0)4 42 42 30 20  
F: +33 (0)4 42 81 29 29  
E: info@sicomin.com  
[www.sicomin.com](http://www.sicomin.com)